

IV. Tafel.

Z	Log. r	Diff. für 1 Min.	m	n
78° 0'	2.4424	0.00060	0.003	0.030
10	2.4484	61	3	31
20	2.4544	61	3	32
30	2.4605	62	3	33
40	2.4667	63	3	34
50	2.4730	64	3	35
79 0	2.4793	0.00064	0.003	0.036
10	2.4858	65	4	37
20	2.4923	66	4	38
30	2.4989	67	4	39
40	2.5056	68	4	40
50	2.5124	69	4	41
80 0	2.5192	0.00070	0.004	0.042
10	2.5262	71	4	43
20	2.5333	72	4	44
30	2.5404	73	4	45
40	2.5477	74	5	47
50	2.5551	75	5	48
81 0	2.5626	0.00076	0.005	0.049
10	2.5702	77	5	51
20	2.5780	79	5	52
30	2.5858	80	5	54
40	2.5938	81	6	56
50	2.6020	83	6	58
82 0	2.6102	0.00084	0.006	0.060
10	2.6187	85	6	62
20	2.6272	87	6	65
30	2.6359	89	7	67
40	2.6448	90	7	70
50	2.6538	92	7	72
83 0	2.6630	0.00094	0.007	0.075
10	2.6724	95	8	78
20	2.6819	97	8	81
30	2.6916	99	8	85
40	2.7015	0.00101	9	88
50	3.7117	103	9	91