

IV. Tafel.

Z	Log. r	Diff. für 1 Min.	m	n
84° 0'	2.7220	0.00105	0.010	0.095
10	2.7325	107	10	0.099
20	2.7432	110	10	0.104
30	2.7542	112	11	0.108
40	2.7655	115	11	0.113
50	2.7770	118	12	0.118
85 0	2.7888	0.00121	0.013	0.123
10	2.8009	124	13	128
20	2.8132	126	14	134
30	2.8259	130	15	141
40	2.8388	133	15	148
50	2.8521	136	16	155
86 0	2.8658	0.00140	0.017	0.162
10	2.8798	144	18	171
20	2.8942	148	19	179
30	2.9089	152	20	189
40	2.9241	157	22	0.199
50	2.9398	161	23	0.210
87 0	2.9559	0.00166	0.024	0.221
10	2.9725	171	26	234
20	2.9896	177	28	248
30	3.0073	182	30	262
40	3.0255	188	32	278
50	3.0444	195	34	295
88 0	3.0639	0.00202	0.037	0.314
10	3.0840	209	40	334
20	3.1049	217	43	356
30	3.1266	225	46	380
40	3.1491	234	50	406
50	3.1725	243	55	434
89 0	3.1968	0.00253	0.059	0.485
10	3.2222	264	65	499
20	3.2486	276	71	537
30	3.2762	288	78	579
40	3.3051	302	86	625
50	3.3353	317	95	677
90 0	3.3670		0.106	0.734